

# RubberSource<sup>INC.</sup>

## PVC Tile – 2'x2'x3/8"

### Technical Specifications

<b>Property</b>	<b>Tuf-Loc</b>
Coverage (Per tile)	4 square feet
Dimensions (Finished Surface)	24" x 24"
Recycled Plastic Content	100%
Thickness	3/8"
Wear Surface	Full Thickness
Weight (per tile)	6 lbs
Abrasion Resistance (grams weight loss)	<0.05 gram
Coefficient of Friction (conforms to ADA recommendations)	0.70
Critical Radiant Flux (watts/cm <sup>2</sup> )	>0.45
Fire Rating	Class 1
Static Load Resistance (psi)	1,000
Density (ASTM D792-88)	1.3 gram / cc
Brittleness (ASTM D745-73)	-24 degrees C
Elongation (ASTM D638-77)	350%
Tensile Strength (STM D2863-77)	2000 psi
Waterproof	Yes

Also resistant to: Oil, gasoline, most solvents, caustics, mold, mildew, water, ozone, abrasion aging.  
Retards the development of bacteria.

Note: Tiles are made from recycled materials which may vary from shipment to shipment, and the following material specifications are therefore a median description only. Actual specifications with regard to density, brittleness, elongation, and tensile strength may vary as much as 15% above or below the median figures represented above.