

## Safety Data Sheet

**RS-5610**

---

### Section 1. Identification

**Common name :** RS-5610

**Product Code :** RS-5610

**Synonym :** Not applicable

**Material uses :** Unvulcanized rubber compound

**Supplier / Manufacturer:**

**Soucy Techno**

2550, St-Roch Sud

Sherbrooke

Québec, Canada, J1N 2R6

Phone: 1-819-864-4284

**In case of emergency:**

**CANUTEC : (613) 996-6666**

**Or call your local Emergency Health Services Center.**

---

### Section 2. Hazards identifications

**Classification :**



Acute hazards to the aquatic environment, Short term, Category 1

Acute hazards to the aquatic environment, Long term, Category 1

**Signal word :** Warning

**Hazard statements:**

H315: Causes skin irritation.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long-lasting effects.

**Precautionary statements:**

P201 : Obtain special instructions before use.

P202 : Do not handle until all safety precautions have been read and understood.

P264: Wash exposed and/or contaminated area thoroughly after handling.

P273 : Avoid release to the environment.

P280 : Wear protective gloves/protective clothing/eye protection/face protection.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P405 : Store locked up.

P501 : Dispose of contents / container by a local waste disposal company according to regional regulations.

### **Section 3. Composition and information on ingredients**

<b>Name</b>	<b>CAS</b>	<b>Concentration %</b>
Carbon black	1333-86-4	10-30
Silica, amorphous	7631-86-9	5-10
Hydrous magnesium silicate	14807-96-6	5-10
Zinc oxide	1314-13-2	1-5
Calcium oxide	1305-78-8	1-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentration applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

---

### **Section 4. First aid measures**

#### **Description of first aid if required:**

Move out of dangerous area. Get medical attention. Show this safety data sheet to the doctor in attendance.

#### **Eye contact:**

Immediately flush eyes with plenty of water. Check for and remove any contact lenses. Rinse eyes thoroughly with water for at least 15 minutes. Get medical attention.

#### **Skin contact:**

Wear protective gloves/protective clothing/eye protection/face protection.

#### **Inhalation:**

Bring the conscious victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, have qualified personnel give artificial respiration. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

#### **Ingestion:**

Wash out mouth with water. Bring the conscious victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick. Do not induce vomiting without advice from poison control center or a doctor. If vomiting occurs, have the individual lean forward with head down to avoid breathing in of vomit. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

#### **Indication of immediate medical attention and special treatment needed, if necessary:**

Do not give anything by mouth to an unconscious victim. Get medical attention.

#### **Most important acute symptoms and effects:**

No known specific effects and/or symptoms

#### **Most important delayed symptoms and effects:**

No known specific effects and/or symptoms

## **Section 5. Fire fighting measures**

**Flammability of the product :** Flammable

**Flash point :** N/A

**Auto-ignition temperature :** N/A

**Products of combustion :**

Carbon dioxide

Carbon monoxide

Metal oxide

**Special protective actions for fire-fighters :**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media :**

Water spray, Carbon dioxide, Foam, Dry Chemical.

---

## **Section 6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:** Evacuate the area.

**For emergency personnel:** Splash goggles, full suit, chemical resistant gloves. Suggested protective clothing might not be sufficient. Consult a specialist before handling this product.

**Environmental precautions:**

Do not let product enter drains

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container.

---

## **Section 7. Handling and storage**

**Precautions in Handling:**

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash hands and face before eating, drinking and smoking. Do not handle until all safety precautions have been read and understood. Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Store in a cool, dry and well-ventilated place between 41°F (5°C) and 95°F (35°C)

## **Section 8. Exposure controls / personal protections**

### **Control parameters:**

<b>Component</b>	<b>CAS</b>	<b>Value</b>	<b>Control parameters</b>	<b>Basis</b>
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	ACGIH
		TWA	3.5 mg/m <sup>3</sup>	CNESST
Silica, amorphous	7631-86-9	TWA	80 mg/m <sup>3</sup>	OSHA
		TWA	6 mg/m <sup>3</sup>	NIOSH
		PEL	6 mg/m <sup>3</sup>	California permissible exposure limits
Hydrous magnesium silicate	14807-96-6	TWA	2 mg/m <sup>3</sup>	NIOSH
		TWA	2 mg/m <sup>3</sup>	ACGIH
		PEL	2 mg/m <sup>3</sup>	California permissible exposure limits
Zinc oxide	1314-13-2	TWA	2 mg/m <sup>3</sup> (inhalable fraction)	ACGIH
		STEL	10 mg/m <sup>3</sup> (inhalable fraction)	ACGIH
		TWA	5 mg/m <sup>3</sup>	OSHA
		TWA	5 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Calcium oxide	1305-78-8	TWA	5 mg/m <sup>3</sup>	OSHA
		TWA	2 mg/m <sup>3</sup>	ACGIH
		PEL	2 mg/m <sup>3</sup>	California permissible exposure limits

### **Engineering controls:**

Use mechanical exhaust or laboratory fume hood to avoid exposure.

### **Personal protective equipment:**

Personal protective equipment should be selected based on the task being performed and the risks involved. Equipment should be approved by a specialist before handling the product.

### **Eyes:**

Wear safety glasses when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, gases and dusts.

### **Skin/body:**

Wear a lab coat or any other appropriate protective clothing.

### **Respiratory:**

If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

### **Hands:**

Wear chemical resistant protective gloves when a risk assessment indicates this is necessary.

## **Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Black

**Odour:** Typical odour of black rubber

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Not applicable

**Flash point:** Data not available

**Auto-ignition temperature:** Data not available

**Decomposition temperature:** above 260°C / 500°F

**pH:** Data not available

**Solubility:** Insoluble

**Density:** 1.19 to 1.23

---

## **Section 10. Stability and reactivity**

### **Chemical reactivity:**

Stable under recommended storage conditions.

### **Reactivity conditions:**

When heated, the rubber polymerizes

### **Conditions to avoid:**

Avoid excessive heat.

### **Incompatible materials:**

Strong oxidizing agents

### **Hazardous decomposition products:**

We find in major part some carbon monoxide and dioxide, due to carbon black and hydrocarbon, at all temperatures, possible emission of sulfur, nitrogen and formaldehyde.

---

## **Section 11. Toxicological information**

### **Acute toxicity:**

<b>Component</b>	<b>CAS</b>	<b>Value</b>
Carbon black	1333-86-4	DL <sub>50</sub> Oral : Rat > 8000 mg/kg DL <sub>50</sub> Cutaneous : Rabbit > 3000 mg/kg
Silica, amorphous	7631-86-9	No data available
Hydrous magnesium silicate	14807-96-6	No data available
Zinc oxide	1314-13-2	DL <sub>50</sub> Oral : Mouse = 7950 mg/kg
Calcium oxide	1305-78-8	No data available

**Skin corrosion/irritation :**

May cause skin irritation.

**Serious eye damage/irritation:**

May cause eye irritation.

**Respiratory or skin sensitisation:**

Not applicable

**Gem cell mutagenicity:**

Not applicable

**Carcinogenicity:**

**Carbon black**

contained in this material is totally bounded to the polymer, so cannot be inhaled under conditions of intended product use.

**Reproductive toxicity:**

Not applicable

**STOT- Single exposure:**

Not applicable

**STOT- repeated exposure:**

Not applicable

**Aspiration hazard:**

Not applicable

**Information on likely route of exposure:**

Not applicable

**Section 12. Ecological information**

**Ecological data for aquatic environments:**

Component	CAS	Value
Carbon black	1333-86-4	CL <sub>50</sub> - Danio rerio 1000 mg/L - 96h CE <sub>50</sub> - Daphnia magna 5600 mg/L - 24h CE <sub>50</sub> - Desmodesmus subspicatus 10000 mg/L - 72h
Silica, amorphous	7631-86-9	No data available
Hydrous magnesium silicate	14807-96-6	No data available
Zinc oxide	1314-13-2	CL <sub>50</sub> - Oncorhynchus mykiss (rainbow trout) 1.1 ppm - 96h CL <sub>50</sub> - Daphnia magna 0.098 mg/L - 48h CE <sub>50</sub> - Pseudokirchneriella subcapitata 0.042 mg/L - 72h
Calcium oxide	1305-78-8	CL <sub>50</sub> - Cyprinus carpio 1070 mg/L - 96h

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Zinc oxide: Very toxic to aquatic life with long lasting effects if discharged in waters.

---

**Section 13. Disposal considerations**

**Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers. Place the containers in storage area of dangerous chemical waste.

---

**Section 14. Transportation information**

No TDG/DOT/IMDG/IATA Classification  
Special precautions for user: Not available.

---

**Section 15. Regulatory information**

**SARA 302:**

No chemicals in this material are subject to the reporting requirements of SARA Title III, section 302.

**SARA 313:**

The following components are subject to reporting levels established of SARA Title III, section 313.

Zinc oxide CAS-No 1314-13-2

**SARA 311/312:**

Chronic Health Hazard

**Massachusetts Right To Know Components:**

Carbon black	CAS-No 1333-86-4
Amorphous silica	CAS-No 7631-86-9
Hydrous magnesium silicate	CAS-No 14807-96-6
Zinc oxide	CAS-No 1314-13-2
Calcium oxide	CAS-No 1305-78-8

**Pennsylvania Right To Know Components:**

Carbon black	CAS-No 1333-86-4
Amorphous silica	CAS-No 7631-86-9
Hydrous magnesium silicate	CAS-No 14807-96-6
Zinc oxide	CAS-No 1314-13-2
Calcium oxide	CAS-No 1305-78-8

**New Jersey Right To Know Components:**

Carbon black	CAS-No 1333-86-4
Hydrous magnesium silicate	CAS-No 14807-96-6
Zinc oxide	CAS-No 1314-13-2
Calcium oxide	CAS-No 1305-78-8

### California Proposition 65 Components:

Carbon black

CAS-No 1333-86-4

Hydrous magnesium silicate

CAS-No 14807-96-6

(Carbon black and hydrous magnesium silicate in this preparation, due to its bound form, do not present this carcinogenic risk)

---

## **Section 16. Additional information**

### **Date of issue:**

2018-11-22

### **Version:**

1.00

### **Elaborated by:**

Soucy Techno

### **Notice to reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan Inc., nor Soucy Techno Inc., nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### **Key to abbreviations:**

CANUTEC : Canadian Transport Emergency Centre

CAS : Chemical Abstracts Service (division of American Chemical Society)

TWA : Time-Weighted Average limit

STEL : Short-Term Exposure limit

PEL: Permissible Exposure limit

ACGIH : American Conference of Governmental Industrial Hygienists

CNESST : Commission des Normes, de l'Équité, de la Santé et de la Sécurité du Travail

OSHA : Occupational Safety and Health Administration

GHS : Globally Harmonized System of classification and labelling of chemicals

IMDG : International Maritime Dangerous Goods

TDG : Transportation of Dangerous Goods regulations

DOT : Department Of Transportation regulation

IATA : International Air Transport Association

### **References:**

- *Répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *The Globally Harmonized System of Classification and Labelling of Chemicals (GHS) <http://www.hc-sc.gc.ca/a>*